

# 628

## Dial Thermometer, distance reading with capillary



628.000

### Precision distance thermometer

Special measuring system for cold with short ranges: better reading

°C or °F:

-60... +32°C, -20... +60°F

**Ø Dimensions:**

2-1/2", 3", 4"

**□ Dimensions:**

96 x 96, 144 x 144mm

**Case:**

Ø AISI 304 (mounting G-H-I)

□ steel black (mounting I)

**Capillary:**

Copper + PVC protection (15-30 FT)

**Bulb:**

Plain in chromed brass

**Accuracy:**

+/- 1°C



629.040

### Thermo diesel - Distance reading for exhaust gases

**Ø Dimensions:**

2-1/2", 3", 4", 6"

Standard type TDC 80 (G)

**Mounting:**

G - H - I - K

**Case + mechanism:**

AISI 304

**Filling:**

High density silicon oil

**Bulb:**

St. St., Ø 10-13 mm

**Connection:**

M - Thread 1/2" or 3/4" BSP or else

**Dual range:**

+50... +650°C / 120... +1200°F



628.085

### Refrigeration - low cost remote thermometer

**Ø Dimensions:**

2-1/2", 3", 4"

**Mounting:**

G - H

**Case:**

Steel grey enameled

**Capillary:**

Copper with PVC protection

**Standard lengths:**

1.5 - 3.5m

**Bulb:**

Plain in chromed brass

**Range**

-40... +40°C (-50... +50°C)

**Accuracy:**

+/- 2% F.S.D.



629.050

### Thermo diesel - Distance reading with electr. device for exhaust gases

**Ø Dimensions:**

4", 6"

**Mounting:**

G - H - I - K

**Case + mechanism:**

AISI 304

**Bulb:**

Steel, Ø 10-13 mm  
(with or without thermowell)

**Connection:**


M - Thread 1/2" or 3/4" BSP

**Range:**

+100... +600°C (etc.)

**Electr. contact:**

1 MAX / 380 V.a.c. / 30 VA



628.080

### Refrigeration industry distance thermometer

**□ Dimensions:**

30 x 60 / 72 x 72

**Case:**

Platic ABS

**Mounting:**

I - Flush - U - Clamp fixing

**Capillary:**

Copper with PVC protection

**Length:**

5 FT (1.5m)

**Bulb:**

Plain in copper

(with or without thermowell)

**Range:**

-40... +40°C